



TG-K10AT

FEATURES

- Same frequency / different frequency
- PC Program Function
- Initialization
- Channel step 5k/ 6.25k/ 10k/ 12.5k/ 25k
- CTCSS/DCS function
- Voice prompt
- Input Frequency directly by keypad
- Display Channel+ Frequency mode
- Monitor and scan function
- Switch power between "HI" and "LOW"

FEATURES

- Auto battery saving function
- Low power alarm, when the power is low, it sends the sound signal to alarm you change the battery.
- Scanning function: frequency and channel scan
- Earphone / microphone / auto charger jack, convenient for answering and charging.



GENERAL

Frequency range	VHF:136-174MHz UHF: 440-480MHz	Operating Voltage	7.2V
Channel	100	Antenna Impedance	50Ω
Channel Spacing	25 /12.5/ 10/ 6.25/ 5KHz	Operating Temperature	-20°C~+ 50°C
Battery	4000mAh Polymer Li-ion Battery	Frequency Stability	±2.5ppm
Size(mm)	138*62*37mm (without antenna)	Packing(pcs)	20 or 40PCS/CTN

TRANSMITTER

Output Power	10W
Modulation	16KΦF3E/11KΦF3E
Maximum Deviation	≤5.0KHz/ ≤2.5KH
Spurious Emission	≤65dB/ ≤60dB
Audio Distortion	≤10%

RECEIVER

Sensitivity	≤0.25/0.28μV
Adjacent Channel Selectivity	65/60dB
Intermodulation	65/60dB
Spurious Response Rejection	70dB
S/N	45/40dB
Rated Audio Power Output	≤0.5W
Rated Audio Distortion	≤10%

STANDARD ACCESSORIES



OPTIONAL ACCESSORIES

